



DN-205W Two-Way In-Wall Speaker

Key Features:

- Two 5-1/4" carbon fiber woofers
- 1" silk and aluminum dome swivel tweeter
- Full-range frequency response
- 50W power handling (100W peak)
- Paintable, magnetic speaker grille
- EN 54-24 compliant

Overview:

The Denon Professional DN-205W two-way wall speaker is designed for commercial installations and is compatible with 70V/100V/8-ohm systems. The assembly is composed of two 5-1/4 inch carbon fiber woofers for superior bass and mid-range reproduction, and a 1-inch silk dome aluminum tweeter for smooth high-end.

Along with full-range response, the unit also features a two position high-frequency roll-off for additional acoustic control. The paintable, magnetic grille enables the DN-205W to completely blend into its surroundings for a professional, clean installation.

Specifications:

- System Specification
 - Low Frequency Drivers:
 - 2x 5.25" (133mm) carbon fiber woofers
 - High Frequency Driver:
 - 1" (25mm) aluminum and silk swivel dome tweeter
 - Frequency Response:
 - 62 - 20kHz
 - High-frequency Roll-off:
 - Two positions, -3dB and -6dB
 - Power Handling:
 - 50W RMS (100W peak)
 - Sensitivity:
 - 88dB (1W/1m)
 - Speaker Connection:
 - Push terminals for wire up to 14AWG
 - Regulatory Compliance:
 - EN 54-24

- Transformer Power Taps
 - 70V:
 - 30, 15, 7.5W
 - 100V:
 - 30, 15W
 - Bypass:
 - 8Åçâ€ŽÃ¡
- Physical
 - Grille Material:
 - Steel
 - Overall Dimension:
 - 14.7 x 7.4 x 3.8" (373 x 187 x 98mm)
 - Cut-out Hole:
 - 13.3 x 6" (338 x 152mm)
 - Wall Clearance:
 - 3.66" (93mm)
 - Weight:
 - 7.7 lbs. (3.5kg)