



Commander Sport

Water-Resistant Portable P.A. Speaker

Key Features:

- Two-way design / 8-inch woofer & 3-inch tweeter
- IPX4 water-resistant rating sealed box design
- Tempo control
- · Battery or AC-powered
- Handheld wireless microphone transmitter included
- · Bluetooth 4.0 playback
- SD/USB media playback
- · XLR combo Mic/Line input
- 3.5mm TRS AUX input

Overview:

Specifications:

- Speaker
 - Tweeter:
 - 3" (80mm)
 - Woofer:
 - 8" (203mm)
 - · Power:
 - 120W continuous
 - Frequency Response:
 - 20 20 kHz
 - Waterproof:
 - IXP4
- Connectors
 - (1) XLR/1/4" TRS combo jack
 - o (1) 1/4" (6.35mm) output
 - o (1) 1/8" (3.5mm) input
 - (2) USB ports

The Commander Sport is an all-in-one, water-resistant, subcompact PA system. This portable system operates on its internal rechargeable battery or AC power. Because of its IPX4 water-resistant design, it can be used in applications around swimming pools, water parks, and outdoor venues. A handheld UHF wireless microphone is included, along with the capability to play audio from Bluetooth®-enabled devices, USB, and SD media. There is also an XLR/TRS combo jack for a wired MIC/LINE input. Tempo control is also featured for custom playback during exercise and water aerobics. This two-way speaker has all the features required for professional sound on-the-go, along with a luggage handle and wheels for easy transport and quick set-up.

- (1) IEC AC power input
- Wireless Microphone**
 - Power
 - 2 x AA alkaline batteries
 - Operating Frequency:
 - UHF 584 608 MHz
 - Available Channels:
 - **1**6
 - **Check downloads section for complete worldwide UHF Frequency List
- . Bluetooth Specifications
 - Version:
 - **4.0**
 - Profiles:
 - A2DP, AVRCP
 - Range:
 - Up to 60-feet (20m)*
 - Maximum Transmission Power:
 - +4 dBm
 - Frequency:
 - 2.4 2.48 GHz
- Power
 - · Connection:
 - IEC
 - Input Voltage:
 - 100 240 VAC, 50/60 Hz
 - Fuse:
 - T2AL 250V
 - Consumption:
 - 80W
- Battery
 - Battery:
 - 12V 7Ah
 - Battery Life:
 - up to 40 hours
 - Battery Recharge Time:
 - 8 hours
- Dimensions (w x d x h):
 - 17.7" x 8.9" x 20.1" (449 x 228 x 510mm)
- · Weight:
 - o 25.8 lbs (11.7 kg)
- *Bluetooth and wireless reception range are affected by walls, obstructions
 and movement. For optimal performance, place the product in the center of
 the room so it is unobstructed by walls, furniture, etc.

UHF Wireless MIC TX Frequency list (USA:584~608MHz)

Channel	Frequency(MHz - Group 1)	Frequency(MHz - Group 2)			
1	584.000	589.600			
2	584.350	589.950			
3	584.700	590.300			
4	585.050	590.650			
5	585.400	591.000			
6	585.750	591.350			
7	586.100	591.700			
8	586.450	592.050			
9	586.800	592.400			
10	587.150	592.750			
11	587.500	593.100			
12	587.850	593.450			
13	588.200	593.800			
14	588.550	594.150			
15	588.900	594.500			
16	589.250	594.850			
UHF Wireless MIC TX Frequency list					
(EU:863~865MHz) Channel Frequency(MHz)					
1	863.300				
2	863.580				
3	863.860				
4	864.140				
5	864.420				
•	004 700				

1	863.300
2	863.580
3	863.860
4	864.140
5	864.420
6	864.700

UHF Wireless MIC TX Frequency list (Japan:806.125~809.75MHz)

Channel Frequency(MHz)

1	806.375
2	806.625
3	806.875
4	807.125
5	807.375
6	807.625
7	807.875
8	808.125
9	808.375
10	808.625
11	808.875
12	809.125
13	809.375