



DN-508MX 8-Zone Mixer with RS-232c and IP Control

Key Features:

- 6 mic/line inputs
- 4 ST inputs
- 1 aux input on front and rear
- 8 zone outputs
- Professional-grade grounding and sound quality
- Remote controllability using TCP/IP, RS-232, and RS-422
- 3-band equalizer for all inputs
- 5-band equalizer for all zone outputs
- Delay and dynamics function for all zone outputs

Overview:

The DN-508MX and 508MXA Zone Mixers are refreshingly uncomplicated, high-performance solutions for controlling and routing up to eight audio sources in multi-room venues. Special attention has been paid to the design of the front panel interface to make them intuitive and easy to operate, which makes the “learning curve” on these products very short. The 508MXA has on-board zone amplification for added flexibility when configuring a specific system with different requirements.

Typical applications include restaurants, hotels, museums, nightclubs, sports bars and large corporate offices. Both

Specifications:

- Audio Specification
 - Frequency Response:
 - 20 Hz – 20 kHz (+0.5 dB)
 - Dynamic Range:
 - > 109 dB (A-weighted)
 - Signal-to-Noise Ratio:
 - > 89 dB (A-weighted)
 - Headroom:
 - > 20 dB
 - Mic Input EIN:
 - < -127 dBu (Rs = 150 Ω, DIN)
 - Mic Input CMRR:
 - > 80 dB
 - Maximum Gain:
 - 88 dB (Mic Input to Master Output)
 - Channel Separation:
 - < -100 dB
 - THD+N (Mic/Line Inputs):

mixers have remote controllability via RS-232C and IP for the commercial installations. The DN-508MX and 508MXA also have several features dedicated for professional use such as a professional grade head-amp, MIC/LINE PAD, full BTL balanced outputs, 3-band EQ for inputs, 5-band EQ for outputs, Priority, Delay, Dynamics, system control application (Web remote), and scheduling function to operate automatically for optimum energy efficiency.

A Web-based GUI makes it simple to control every function of the unit, from whatever device is most convenient for the user.

- < 0.05%
 - THD+N (ST Inputs):
 - < 0.01%
- Analog Inputs
 - Mic Inputs
 - Maximum:
 - -40 to -20 dBu (+4 dBu)
 - Unity:
 - -60 to -40 dBu (-16 dBu)
 - Line Inputs
 - Maximum:
 - -20 to 0 dBu (+24 dBu)
 - Unity:
 - -40 to -20 dBu (+4 dBu)
 - ST Inputs
 - Maximum:
 - +18 dBV
 - Unity:
 - 0 dBV
 - Aux Inputs
 - Maximum:
 - +18 dBV
 - Unity:
 - 0 dBV
- Analog Outputs
 - Zone Outputs
 - Maximum:
 - +24 dBu
 - Unity:
 - +4 dBu
- Effects
 - Equalization (3-Band, Inputs)
 - SHH 100 Hz – 20 kHz (+18 dB)
 - PEQ 100 Hz – 20 kHz (+18 dB), Q: 0.1–63.0
 - SHL 20 Hz – 20 kHz (+18 dB)
 - Equalization (5-Band, Outputs)
 - High PEQ 100 Hz – 20 kHz (+18 dB), Q: 0.1–63.0
 - Mid-High PEQ 100 Hz – 20 kHz (+18 dB), Q: 0.1–63.0
 - Mid PEQ 100 Hz – 20 kHz (+18 dB), Q: 0.1–63.0
 - Mid-Low PEQ 100 Hz – 20 kHz (+18 dB), Q: 0.1–63.0
 - Low PEQ 20 Hz – 20 kHz (+18 dB), Q: 0.1–63.0
 - Delay
 - Attenuation 0–1000 ms
 - Automatic Gain Control (AGC)

- Compensation 1–5
 - Response Time 100–500 ms
 - Noise Gate < -80 dBFS
- Priority Attenuation (1st & 2nd priorities)
 - Threshold -74 to -20 dBFS
 - Attenuation $-\infty$ to 0 dB
 - Attack Time 0–300 ms
 - Hold Time 1–1960 ms
 - Release Time 3–4270 ms
- Dynamics (Compressor/Limiter)
 - Threshold -92 to -20 dBFS
 - Ratio 1.0:1 – 20.0:1, ∞ :1
 - Attack Time 0–120 ms
 - Release Time 3–4270 ms
 - Gain 0 to +20 dB
 - Knee Hard, 1–5
- Auto Fade Out/In for Source Selector
 - Attenuation -30 dB
 - Attack Time 100 ms
 - Hold Time & Mixing 100 ms
 - Release Time 100 ms
- Communication
 - RS-232C
 - Connectors:
 - 9-pin D-Sub female connector (Remote input), 9-pin D-Sub male connector (Remote Extend output)
 - Speed:
 - 9600/38400 bps
 - Power:
 - +5 V via D-Sub connection
 - RS-422
 - Connector:
 - RJ-45
 - Speed:
 - 38400 bps
 - Terminal:
 - 110 Ω on/off
 - Power:
 - +5 V via RJ-45 connection
 - Ethernet
 - Connector:
 - LAN port
 - Standards:
 - Ethernet 10/100 Base
- Level Indicators
 - Mic/Line:
 - 1 LED (green-amber-red) per mic/line input
 - Source:

1 LED (green-amber-red) per ST input

- Output:
 - 1 LED (green-amber-red) per zone
- Peak Indication:
 - -1 dB to 0 dB
- Connections
 - (6) 3-pin Euroblock inputs (1 hot, 1 cold, 1 ground)
 - (1) stereo RCA auxiliary input
 - (1) stereo 1/8" (3.5 mm) auxiliary input
 - (4) stereo RCA ST inputs
 - (4) 5-pin Euroblock outputs (2 hot, 2 cold, 1 ground)
 - (1) LAN port
 - (1) RJ11/RJ14 port, RS-422
 - (1) 9-pin D-Sub female connector, RS-232C
 - (1) 9-pin D-Sub male connector, RS-232C
 - (1) IEC power input
- Environmental
 - Temperature:
 - 41–95°F / 5–35°C
 - Humidity:
 - 25–85%, non-condensing
- General
 - Power Connection:
 - IEC
 - Power Requirement:
 - 100–240V AC, 50/60 Hz
 - Power Consumption:
 - 30 W
 - Dimensions (WDH, with rack ears):
 - 19.0 x 13.5 x 1.8" (482 x 344 x 46.3mm)
 - Weight:
 - 8.55 lbs. (3.88 kg)